

A

BOLT TANK  
TO BULKHEAD  
4 POSITIONS

POSITION A MIRROR  
IN A SUITABLE  
PLACE TO VIEW  
FUEL CONTENTS

15 LITRE  
PLASTIC TANK

DRILL FUEL OUTLET  
PIPE AS SHOWN TO  
PREVENT FUEL STARVATION  
IF ONE HOLE BLOCKS

GLUE A SPRUCE WEDGE  
TO TOP OF WING BOX  
SCREW AN 8MM BIRCH PLY  
TRIANGULAR SUPPORT  
BRACKET IN PLACE  
FIX TO SEAT BACK  
WITH A 1,6 6082T6  
AS SHOWN

TAP  
NYLON FILTER  
FUEL TRANSFER  
BULB  
TO ENGINE

FUEL TAP  
RUN PIPE FROM  
TANK THEN BACK  
TO ENGINE VIA  
ACCESSIBLE TRANS  
BULB

SIT TANK ON  
FOAM PAD  
BOND PAD TO SEAT  
WITH EVOSTICK

TANK AVAILABLE  
SEE INTERNET

FUEL CONSUMPTION OF THE BLACK BULL  
ENGINE IS GIVEN AS 4 TO 5L/HOUR  
15L TANK WILL GIVE A MAX ENDURANCE  
OF 3 HOURS

MW9B-57  
FUEL TANK

SEAT TOP SUPPORT